
## BugBrand PostcardWeevil 2009

Tri-Osc Ring-Mod Porta-Synth



#### OSC1 RM2 Driver → Contraction Level → Speaker Speaker

### Instructions for use -> experiment!

#### Notes:

•Battery power only!

•The mini-jack output only works with a *mono* 3.5mm plug. Plugging in will mute and remove power from the onboard MiniAmp


•Beware of metal / conductive materials shorting out the underside of the circuit, especially during transport. If short circuited, the battery may overheat and cause damage. If in doubt, remove the battery during transport.


•For questions or comments email <u>tom@bugbrand.co.uk</u>



# BugBrand PostcardWeevil 2009

Tri-Osc Ring-Mod Porta-Synth





Instructions for use -> experiment!

### Notes:

•Battery power only!

 $\bullet The mini-jack output only works with a mono 3.5mm plug. Plugging in will mute and remove power from the onboard MiniAmp$ 


•Beware of metal / conductive materials shorting out the underside of the circuit, especially during transport. If short circuited, the battery may overheat and cause damage. If in doubt, remove the battery during transport.


•For questions or comments email tom@bugbrand.co.uk



# BugBrand PostcardWeevil 2009

Tri-Osc Ring-Mod Porta-Synth





## Instructions for use -> experiment!

Notes:

#### •Battery power only!

•The mini-jack output only works with a *mono* 3.5mm plug. Plugging in will mute and remove power from the onboard MiniAmp

•Beware of metal / conductive materials shorting out the underside of the circuit, especially during transport. If short circuited, the battery may overheat and cause damage. If in doubt, remove the battery during transport.

•For questions or comments email tom@bugbrand.co.uk

